

OPTICAL RECORDING MEDIUM, METHOD RECORDING OPTICAL RECORDING MEDIUM, AND RECORDER

Publication number: AU2003289079 (A1)

Publication date: 2004-07-14

Inventor(s): KUBO HIDEYUKI; TAKESHIMA HIDEHARU

Applicant(s): MITSUBISHI CHEM CORP

Classification:

- international: G11B7/007; G11B7/00; G11B7/125; G11B7/24; G11B7/007; G11B7/00; G11B7/125; G11B7/24; (IPC1-7): G11B7/0045; G11B7/007; G11B7/125; G11B7/24

- European: G11B7/007R

Application number: AU20030289079 20031212

Priority number(s): JP20030202321 20030728; JP20020370934 20021220; JP20030098320 20030401; WO2003JP15985 20031212

Also published as:

EP1575035 (A1)
EP1575035 (A8)
EP1575035 (A4)
US2005226116 (A1)
US2005226116 (A1)

more >>

Abstract not available for AU 2003289079 (A1)

Abstract of corresponding document: EP 1575035 (A1)

In an optical recording medium having a plurality of recording layers on which information can be recorded by irradiating a laser beam from one side thereof, an optimum recording power to each of the recording layers can be determined. The optical recording medium has a plurality of recording layers on which information can be recorded by irradiating a laser beam from one side thereof, and each of the recording layers has a power calibration area (PCA) (52),(61) for optimizing the intensity of the laser beam.



Data supplied from the esp@cenet database — Worldwide